

MATERIAL SAFETY DATA SHEET

Product Name 5.56 (BULK)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name CRC INDUSTRIES (AUST) PTY LIMITED

Address 9 Gladstone Road, Castle Hill, NSW, AUSTRALIA, 2154

 Telephone
 (02) 9634 2088

 Fax
 (02) 9680 4914

 Emergency
 (02) 9634 2088

 Email
 info@crcind.com.au

 Web Site
 http://www.crcind.com.au/

Synonym(s) 5.56 (BULK) • 5006 - PRODUCT CODE • 5007 - PRODUCT CODE • 5009 - PRODUCT CODE • 5011 -

PRODUCT CODE • CRC 5-56 (BULK) (FORMERLY)

Use(s) LUBRICANT • PENETRANT

SDS Date 01 Apr 2010

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

RISK PHRASES

R20/22 Harmful by inhalation and if swallowed.

R33 Danger of cumulative effects.

R36/37/38 Irritating to eyes, respiratory system and skin.
R65 Harmful: May cause lung damage if swallowed.

SAFETY PHRASES

S23 Do not breathe gas/fumes/vapour/spray (where applicable). S36/39 Wear suitable protective clothing and eye/face protection.

S51 Use only in well ventilated areas.

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.None AllocatedDG ClassNone AllocatedSubsidiary Risk(s)None AllocatedPacking GroupNone AllocatedHazchem CodeNone AllocatedEPGNone Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
PETROLEUM DISTILLATE(S)	Not Available	Not Available	>60%
MINERAL OIL (SOLVENT REFINED)	Not Available	Not Available	10-30%
CORROSION INHIBITOR(S)	Not Available	Not Available	<10%



Product Name 5.56 (BULK)

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue

flushing with water until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed,

do not induce vomiting.

Advice to Doctor Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Fire and Explosion

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.

Hazchem Code None Allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage

Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.

7. STORAGE AND HANDLING

Storage

Store in a cool, dry, well ventilated area, removed from oxidising agents, acids, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation systems. Store as a Class C1 Combustible Liquid (AS1940).

Handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

Ingredient	Deference	-	TWA		STEL	
	Reference	ppm	mg/m3	ppm	mg/m3	
Mineral Oil Mist	ASCC (AUS)		5			
Oil mists	ASCC (AUS)		5			

Biological Limits

No biological limit allocated.

Engineering Controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

Wear splash-proof goggles and neoprene or nitrile gloves. When using large quantities or where heavy contamination is likely, wear: coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator.





9. PHYSICAL AND CHEMICAL PROPERTIES

Page 2 of 5 RMT



5.56 (BULK) **Product Name**

9. PHYSICAL AND CHEMICAL PROPERTIES

CLEAR AMBER LIQUID INSOLUBLE Appearance Solubility (Water)

Odour PLEASANT ODOUR **Specific Gravity** 0.81 NOT AVAILABLE % Volatiles 82 %

Flammability CLASS C1 COMBUSTIBLE Vapour Pressure 0.23 mm Hg

Vapour Density > 1 (Air = 1)Flash Point 70°C **Boiling Point** 193°C (Initial) 12 % **Upper Explosion Limit Melting Point NOT AVAILABLE Lower Explosion Limit** 1.4 %

Evaporation Rate 0.05 (n-Butyl acetate = 1)

Autoignition Temperature 550°C

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid heat, sparks, open flames and other ignition sources.

Material to Avoid Incompatible with oxidising agents (eq. hypochlorites), acids (eq. nitric acid), heat and ignition sources.

Decomposition May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Hazardous Reactions Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Low to moderate toxicity - irritant. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. Over exposure may result in central Summary

nervous system (CNS) effects.

Eye Irritant. Contact may result in irritation, lacrimation, pain and redness.

Inhalation Irritant. Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure

may result in nausea, dizziness and drowsiness.

Skin Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis.

Low to moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and Ingestion

drowsiness. Aspiration may result in chemical pneumonitis and pulmonary oedema.

Toxicity Data No LD50 data available for this product.

12. ECOLOGICAL INFORMATION

Environment Aliphatic hydrocarbons behave differently in the environment depending on their size. WATER: Light aliphatics

volatilise rapidly from water (half life - few hours). Bioconcentration should not be significant. SOIL: Light aliphatics biodegrade quickly in soil and water, heavy aliphatics biodegrade very slowly. ATMOSPHERE: Vapour-phase

aliphatics will degrade by reaction with hydroxyl radicals.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Incinerate where available. For small amounts absorb with sand, vermiculite or similar and dispose of to approved

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

None Allocated **Shipping Name**

None Allocated **DG Class** UN No. None Allocated Subsidiary Risk(s) None Allocated None Allocated **EPG** None Allocated **Hazchem Code Packing Group** None Allocated

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and

Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).



Page 3 of 5

16. OTHER INFORMATION

Additional Information

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European Inventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmt.com.au Web: www.rmt.com.au



Page 4 of 5 **RMT**

Reviewed: 01 Apr 2010

Printed: 13 Apr 2010

Product Name 5.56 (BULK)

SDS Date: 01 Apr 2010 End of Report

