

High Performance Soluble Metalworking Fluid



Sol-MB 50 is especially designed for machining of ferrous and aluminium alloys.

- High Performance soluble metalworking fluid
- Unique additives that enhance machining performance and surface finish
- Chlorine and Formaldehyde releasing agent free
- Improves bio-resistance properties - lowers overall operations cost
- Suitable for large central systems and single pump machines

NOTE: Not recommended for use with yellow metals.

Product Code	Description	Pack Description
MAT-SOLMB50-020	SOL MB50	20 Lt Pail
MAT-SOLMB50-200	SOL MB50	200 Lt Drum

MATRIX INDUSTRIAL

High Performance Soluble Metalworking Fluid



Sol-X is especially designed for heavy duty machining of ferrous and non-ferrous metals.

- High Performance soluble metalworking fluid
- Unique additives that enhances machining performance and surface finish
- Chlorine free
- Suitable for large central systems
- Suitable for single pump machines

Product Code	Description	Pack Description
MAT-SOLX-020	SOL-X	20 Lt Pail

MATRIX INDUSTRIAL

Machining Neat Cutting Oil Cut 05 MT



Cut 05 MT is a universal cutting fluid formulated from judiciously selected components.

The balanced additives maximize performance over a wide range of pressures and temperatures seen when machining difficult metals and difficult conditions.

Cut 05 MT has high chemical stability, good cooling properties and minimum tendency to form oil mist. It is recommended for machining of all metals, with excellent performance under heavy operation conditions.

Product Code	Description	Pack Description
MAT-CUT05MT-020	Cutting Oil CUT 05 MT	20 Lt Pail

MATRIX INDUSTRIAL

Premium Grinding Fluid Sol Plus 144 CU



A synthetic coolant, based upon the formulation of selected chemicals in solution which provides an oily grinding fluid totally formaldehyde free.

It is a transparent fluid suitable for all types of grinding applications and for the less arduous machining operations of steel, cast iron and copper.

The product is formulated from selected materials which will not support sump bacteria.

It will not foam or split even under the most turbulent conditions; the product totally rejects tramp oil making it ideal choice as grinding fluid.

The swarf settling and excellent corrosion properties of the product ensure that many months trouble free sump life can be achieved with a single charge of coolant.

Product Code	Description	Pack Description
MAT-SOLPLUS144CU-020	Grinding Fluid Sol Plus 144 CU	20 Lt Pail