

MPR502FG

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

SECTION 1: Identification

1.1. GHS Product identifier

Trade name: MPR502FG

1.2. Recommended use of the chemical and restrictions on use

Recommended uses: Cleaner

1.3. Supplier's details

Supplier

Company: Mouldpro ApS
Address: Baltorpbakken 10
Zip code: 2750
City: Ballerup
Country: DENMARK
E-mail: sales@mouldpro.com
Phone: +45 70 20 31 31
Homepage: www.mouldpro.com

Australian Supplier:

Hales Australia Pty Ltd
ABN: 90 107 200 322
Address: 45 Woodlands Drive,
Braeside VICTORIA 3195
Phone: +61 3 8587 1600
Website: www.hales.com.au
Email: info@hales.com.au

1.4. Emergency phone Number

+ 45 70 20 31 31 (Mouldpro) The emergency telephone is open between 8 a.m. and 4 p.m. on workdays.

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Australia Emergency numbers 24 hours –

Phone: 13 11 26 (Poisons Information Centre Australia)
Phone: 1300 131 001 (ISS First Response Centre)

GHS classification:

Aerosols, Category 1;H222
Aerosols, Category 1;H229
Acute toxicity, Category 5;H313
Skin irritation, Category 2;H315
Serious eye damage, Category 1;H318
Acute toxicity, Category 5;H333

Most serious harmful effects:

Extremely flammable aerosol. Pressurised container: May burst if heated. May be harmful in contact with skin. Causes skin irritation. Causes serious eye damage. May be harmful if inhaled. The product releases organic solvent vapors which may cause drowsiness and dizziness. At high concentrations, the vapors may cause headache and intoxication. Prolonged or repeated inhalation of vapors may cause damage to the central nervous system.

MATERIALS DATA SAFETY SHEET

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

2.2. GHS label elements, including precautionary statements

Pictograms



Signal word:

Danger

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H333	May be harmful if inhaled.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear eye protection/face protection.
P305+351+338+310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

2.3. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No./ EC No./ REACH Reg. No.	Concentration	Notes
Petroleum gases, liquefied (with <0,1% 1,3-Butadiene)	68476-85-7 270-704-2	60 - 100 %	
cyclohexanone	108-94-1 203-631-1 01-2119453616-35	30 - 60 %	
acetone	67-64-1 200-662-2 01-2119471330-49	10 - 20 %	

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

Inhalation:	Seek fresh air. Seek medical advice in case of persistent discomfort.
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Seek medical advice in case of persistent discomfort.
Skin contact:	Remove contaminated clothing. Seek medical advice in case of persistent discomfort. Wash skin with soap and water.
Eye contact:	Open eye wide, remove any contact lenses and flush immediately with water (preferably



MATERIALS DATA SAFETY SHEET

Replaces date: 3/10/2021

Revision date: 1/24/2022

Version: 1.2.0

using eye wash equipment). Seek medical advice immediately. Continue flushing until medical attention is obtained.

Burns: Flush with water until pain ceases. Remove clothing that is not stuck to the skin - seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.

General: Bring the safety data sheet or label when seeking medical advice.

4.2. Most important symptoms/effects, acute and delayed

Irritates mucous membranes in mouth and gastrointestinal tract. Irritating to skin - may cause reddening. Eye contact may result in deep caustic burns, pain, tearing and cramping of the eyelids. Risk of serious eye injury and loss of sight. The product releases organic solvent vapors which may cause drowsiness and dizziness. At high concentrations, the vapors may cause headache and intoxication. Prolonged or repeated inhalation of vapors may cause damage to the central nervous system. May be harmful if inhaled. May be harmful in contact with skin.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptoms. Ensure that medical personnel are aware of the material involved, and take precautions to protect themselves.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

Suitable extinguishing media: Extinguish with powder, foam or water mist. Use water or water mist to cool non-ignited stock.

Unsuitable extinguishing media: Do not use a jet of water, as it may spread the fire.

5.2. Specific hazards arising from the chemical

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released. Heating will cause a rise in pressure in packaging with a risk of bursting. CAUTION! Aerosol containers may explode.

5.3. Special protective actions for fire-fighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapor and smoke gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel: Stay upwind/keep distance from source. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment. Provide adequate ventilation. Smoking and naked flames prohibited. Wear gloves. Wear safety goggles.

For emergency responders: In addition to the above: Protective suit is recommended.

6.2. Environmental precautions

Avoid unnecessary release to the environment.

6.3. Methods and materials for containment and cleaning up

Wipe up drops and splashes with a cloth.

6.4. Reference to other sections

See section 8 for type of protective equipment.

See section 13 for instructions on disposal.



MATERIALS DATA SAFETY SHEET

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Work under effective process ventilation (e.g. local exhaust ventilation). Running water and eye wash equipment must be available. Smoking and naked flames prohibited. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, drugs, etc. Do not store with the following: Oxidisers. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not expose to heat (e.g. sunlight). Store in a dry, cool, well-ventilated area. Avoid direct sunlight.

7.3. Specific end use(s)

No special uses in addition to identified uses in 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit: Contains no substances subject to reporting requirements

Measuring methods: Compliance with occupational exposure limits may be checked by occupational hygiene measurements.

8.2. Exposure controls

Appropriate engineering controls: Wear the personal protective equipment specified below.

Personal protective equipment, eye/face protection: Wear safety goggles.

Personal protective equipment, hand protection: Wear gloves. Type of material: Nitrile rubber. Breakthrough time has not been determined for the product. Change gloves often. The suitability and durability of a glove is dependant on usage, e.g. frequency and duration of contact, glove material thickness, functionality and chemical resistance. Always seek advice from the glove supplier.

Personal protective equipment, respiratory protection: In case of risk of formation of spray mist, wear respiratory protective equipment with P2 filter.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit
Physical state	Aerosol
Color	Clear
Odour	Solvent
Solubility	No data

Parameter	Value/unit	Remarks
Odour threshold	No data	
Melting point	No data	
Freezing point	No data	
Boiling point or initial boiling point and boiling range	-40 - -2 °C	(LPG)



MATERIALS DATA SAFETY SHEET

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

Flammability	No data	
Lower and upper flammability limit	1.4 - 10.9 vol%	(LPG)
Lower and upper explosion limit	No data	
Flash Point	-104 °C	(LPG)
Auto-ignition temperature	365 °C	(LPG)
Decomposition temperature	No data	
pH (solution for use)	No data	
pH (concentrate)	No data	
Kinematic viscosity	No data	
Viscosity	No data	
Partition coefficient n-octanol/water (log value)	No data	
Vapour pressure	No data	
Density	No data	
Relative density	No data	
Relative vapour density	No data	
Relative density (sat. air)	No data	
Particle characteristics	No data	

9.2. Other information

Other Information: None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with the following: Oxidisers. The product may ignite on contact with e.g. heat or a spark.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

Product vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

10.4. Conditions to avoid

Avoid heating and contact with ignition sources. Avoid direct sunlight. Avoid temperatures >50°C.

10.5. Incompatible materials

Oxidisers.

10.6. Hazardous decomposition products

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

SECTION 11: Toxicological information

11.1. Information on health hazard classes

Acute toxicity - oral

MPR502FG

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	ATE		5400 mg/kg			

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met. Ingestion may cause discomfort.

Copyright © 1995 - 2023 DGOOffice B.V., www.DGOOffice.net

cont.



MATERIALS DATA SAFETY SHEET

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

Acute toxicity - dermal

MPR502FG

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	ATE		3666.67 mg/kg			

May be harmful in contact with skin.

Acute toxicity - inhalation

MPR502FG

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	ATE (vapours)		36.67 mg/l			

May be harmful if inhaled.

Skin corrosion/irritation: Irritating to skin - may cause reddening.

Serious eye damage/eye irritation: Eye contact may result in deep caustic burns, pain, tearing and cramping of the eyelids. Risk of serious eye injury and loss of sight.

Respiratory sensitization or skin sensitization: The product does not have to be classified. Test data are not available.

Germ cell mutagenicity: The product does not have to be classified. Test data are not available.

Carcinogenic properties: The product does not have to be classified. Test data are not available.

Reproductive toxicity: The product does not have to be classified. Test data are not available.

Single STOT exposure: The product does not have to be classified. Test data are not available. If ingested, can be irritating to mucous membranes of the mouth and gastrointestinal tract. The product contains small quantities of organic solvents. When working in large areas in poorly ventilated rooms, the vapors may cause headache and dizziness.

Repeated STOT exposure: The product does not have to be classified. Test data are not available. Prolonged or repeated inhalation of vapors may cause damage to the central nervous system.

Aspiration hazard: The product does not have to be classified. Test data are not available.

11.2. Information on other hazards

Endocrine disrupting properties: None known.

Other toxicological effects: None known.

SECTION 12: Ecological information

12.1. Toxicity

The product does not have to be classified. Test data are not available.

12.2. Persistence and degradability

Expected to be biodegradable. Test data are not available.

12.3. Bioaccumulative potential

No bioaccumulation expected. Test data are not available.

12.4. Mobility in soil



MATERIALS DATA SAFETY SHEET

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

None known.

12.7. Other adverse effects

Potential for photo-chemical formation of ozone.

SECTION 13: Disposal considerations

13.1. Disposal methods

Avoid unnecessary release to the environment. Do not dispose of aerosol sprays in refuse collection, even when empty. The sprays must be sent to the municipal chemical waste collection facility.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS	14.5. Environmental hazards:	The product should not be labelled as an environmental hazard (symbol: fish and tree).
14.3. Transport hazard class(es):	2.1		
Hazard label(s):	2.1		
Hazard identification number:		Tunnel restriction code:	D

Inland water ways transport (ADN)

14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS	14.5. Environmental hazards:	The product should not be labelled as an environmental hazard (symbol: fish and tree).
14.3. Transport hazard class(es):	2.1		
Hazard label(s):	2.1		
Transport in tank vessels:			

Sea transport (IMDG)

14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS	14.5. Environmental hazards:	The product is not a Marine Pollutant (MP).
14.3. Transport hazard class(es):	2.1	Environmental Hazardous Substance Name(s):	
Hazard label(s):	2.1		
EmS:	F-D, S-U	IMDG Code segregation group:	- None -

Air transport (ICAO-TI / IATA-DGR)

Copyright © 1995 - 2023 DGOOffice B.V., www.DGOOffice.net

cont.



MATERIALS DATA SAFETY SHEET

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

14.1. UN number:	1950	14.4. Packing group, if applicable:	
14.2. UN proper shipping name:	AEROSOLS, FLAMMABLE	14.5. Environmental hazards:	The product should not be labelled as an environmental hazard (symbol: fish and tree).
14.3. Transport hazard class(es):	2.1		
Hazard label(s):	2.1		

14.6. Special precautions for user

None.

14.7. Transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question**Special Provisions:** None.**15.2. Chemical Safety Assessment****Other Information:** Chemical safety assessment has not been performed.

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes
1.2.0	1/24/2022	Bureau Veritas HSE - DOL	2,3,9,11,12,15,16
1.1.0	3/10/2021	Bureau Veritas HSE - DOL	8,16

Abbreviations:

PBT: Persistent, Bioaccumulative and Toxic

STOT: Specific Target Organ Toxicity

vPvB: Very Persistent and Very Bioaccumulative

Other Information:

This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with GHS Rev. 7 (2017).

Training advice:

A thorough knowledge of this safety data sheet should be a prerequisite condition.

Classification method:

Calculation based on the hazards of the known components. Test data.

SDS is prepared by

Company: Bureau Veritas HSE Denmark A/S
 Address: Oldenborggade 25-31
 Zip code: 7000
 City: Fredericia
 Country: DENMARK



MATERIALS DATA SAFETY SHEET

Safety Data Sheet

MPR502FG

Replaces date: 3/10/2021

Revision date: 1/24/2022
Version: 1.2.0

E-mail: infohse@dk.bureauveritas.com
Phone: +45 77 31 10 00
Homepage: www.bureauveritas.dk

Country: UN

end of SDS

