Technical Data Sheet

















Foodmax HTF

Premium food grade heat transfer fluid

Description

Foodmax HTF fluids are made with food grade synthetic base fluids. They are formulated to be very thermally and oxidative stable and are further enhanced with proprietary additives that greatly extend their life over normal and other synthetic food grade heat transfer fluids. They provide exceptional performance in a number of food related heat transfer applications.

Foodmax HTF fluids are non toxic and non hazardous, they meet US FDA 21 CFR 178.3570 lubricants for incidental food contact and are NSF HT-1 and InS HT-1 approved.

Applications

Foodmax HTF fluids are used as heat transfer medium in numerous food related applications, designed for systems operating at a maximum temperature of 326 °C. The maximum film temperature is 343 °C.

Benefits

- Excellent thermal & oxidation stability which contributes to long life at very high temperatures
- Very high flash, fire & auto-ignition temperatures for added safety
- Very low volatility and vapour pressures
- High heat capacity and thermal conductivity
- Very good deposit control to help keep system clean
- Low viscosity at operating temperatures for improved pumping efficiency
- Excellent demulsibility and good cold flow properties for smoother start ups

Page 1 of 2

All performance data on this Technical Data Sheet are indicative only and can vary during production

Matrix Specialty Lubricants BV - info@lubes-portal.com - www.lubes-portal.com

18/08/2014 Version 3

Technical Data Sheet

















Typical performance data

	HTF
Density @ 20 °C, kg/l	0,85
Viscosity @ 40 °C, cSt	41
Viscosity @ 100 °C, cSt	6,2
Flash point, °C	226
Auto ignition point, °C	356
Pour point, °C	-10
Carbon residue, %	0.005
Copper strip corrosion, 24hrs @ 100 °C	1a
Distillation range 10% °C	403
Distillation range 90% °C	499
Thermal conductivity (W/ mK) @ 38 °C	0,147
Thermal conductivity (W/ mK) @ 204 °C	0,135
Thermal conductivity (W/ mK) @ 260 °C	0,131
Thermal conductivity (W/ mK) @ 316 °C	0,13
Heat capacity (kj/kg K) @ 38 °C	2,05
Heat capacity (kj/kg K) @ 204 °C	2,60
Heat capacity (kj/kg K) @ 260 °C	2,85
Heat capacity (kj/kg K) @ 316 °C	2,81
Vapor pressure (kPA) @ 38 °C	0,00
Vapor pressure (kPA) @ 204 °C	0,55
Vapor pressure (kPA) @ 260 °C	2,9
Vapor pressure (KPA) @ 316 °C	12,55
InS registration	1794792
NSF registration	138898
Kosher approval	Yes

All performance data on this Techni

Matrix Specialty Lubricants B

18/08/2014 Version 3 Page 2 of 2